


# BLIND RIVETS

## DOMED HEAD - STAINLESS STEEL

### STAINLESS STEEL

T304 STAINLESS STEEL RIVET WITH 304 STAINLESS STEEL MANDREL

Available in Domed Head (R73STST)



Domed Head

RIVET CODE	RIVET DIAMETER D	HOLE SIZE (MM)	RIVET LENGTH L (MM)	GRIP RANGE G (MM)	HEAD DIAMETER H (MM)	HEAD THICKNESS T (MM)	STANDARD STRENGTH N (MIN.)	
							SHEAR	TENSILE
42 43 44 45 46 48	3.2mm	3.3 - 3.4	6.7 8.2 9.7 11.4 13.0 16.2	0.8 - 3.2 3.2 - 4.8 4.8 - 6.4 6.4 - 7.9 7.9 - 9.5 9.5 - 12.7	6.05 - 6.65	1.02	1870	2360
52 53 54 55 56 58	4.0mm	4.1 - 4.2	7.3 8.9 10.5 12.0 13.6 16.8	0.8 - 3.2 3.2 - 4.8 4.8 - 6.4 6.4 - 7.9 7.9 - 9.5 9.5 - 12.7	7.52 - 8.33	1.27	2890	3650
62 63 64 65 66 68 610 612	4.8mm	4.9 - 5.0	8.0 9.5 11.1 12.7 14.3 17.5 20.7 23.8	0.8 - 3.2 3.2 - 4.8 4.8 - 6.4 6.4 - 7.9 7.9 - 9.5 9.5 - 12.7 12.7 - 15.9 15.9 - 19.1	9.04 - 10.01	1.52	4230	5340
82 84 86 88 810 812 814 816	6.4mm	6.5 - 6.6	9.2 12.4 15.5 18.7 21.9 25.1 28.2 31.4	0.8 - 3.2 3.2 - 6.4 6.4 - 9.5 9.5 - 12.7 12.7 - 15.9 15.9 - 19.1 19.1 - 22.2 22.2 - 25.4	12.07 - 13.34	2.03	7570	9350